



CE Declaration of Performance and Marking
Cloburn Quarry Company Ltd
Lanark
ML11 8SR


2019

2797-CPR-572235

EN 13043:2002

0/2mm Red 13043 for the production of bituminous mixtures, product code 09

| | |
|---|--------------|
| Petrographic Classification | Microgranite |
| Particle Size | 0/2 |
| Particle Density | 2.60 |
| Affinity to Bituminous Binders | NPD |
| Percentage of Crushed Particles/Broken Surfaces | NPD |
| Resistance to Fragmentation / Crushing | LA 15 |
| Polished Stone Value | PSV 50 |
| Aggregate Abrasion Value | AAV 10 |
| Resistance to Wear of Coarse Aggregate | MDE 10 |
| Resistance to impact | SZ 18 |
| Magnesium Sulfate Value | MS 18 |
| Abrasion from Studded Tyres | NPD |
| Resistance to Thermal Shock | NPD |
| Iron Disintegration of Air-cooled Blastfurnace Slag | NPD |
| Volume Stability of Steel Slag Aggregates | NPD |
| Emission of Radioactivity | NPD |
| Release of other Dangerous Substances | NPD |
| Water Absorption Value | 0.63% |

| | |
|-----------------------------------|--|
| Declaration of Performance | Cloburn Quarry Company confirms that the Aggregate referred to in this certificate complies with the requirement of BS EN 13043:2002 |
| Certificate of Performance | Certification of Performance with BS EN 13043 is provided under attestation system 2+ |
| Authorised by | Stuart Clingan, Commercial Manager  |
| Date Valid from | 08.11.19 |
| Date valid to | Currently valid |
| Date of Certificate Issue | 08.11.19 |



CE Declaration of Performance and Marking
Cloburn Quarry Company Ltd
Lanark
ML11 8SR

2019

2797-CPR-572235

EN 13043:2002

4/10mm Gc85/20 13043 for the production of bituminous mixtures, product code 03

| | |
|---|--------------|
| Petrographic Classification | Microgranite |
| Particle Size | 4/10 |
| Particle Density | 2.61 |
| Particle Shape | FI20 |
| Cleanliness | f4 |
| Affinity to Bituminous Binders | NPD |
| Percentage of Crushed Particles/Broken Surfaces | NPD |
| Resistance to Fragmentation / Crushing | LA 15 |
| Polished Stone Value | PSV 50 |
| Aggregate Abrasion Value | AAV 10 |
| Resistance to Wear of Coarse Aggregate | MDE 10 |
| Resistance to impact | SZ 18 |
| Magnesium Sulfate Value | MS 18 |
| Abrasion from Studded Tyres | NPD |
| Resistance to Thermal Shock | NPD |
| Iron Disintegration of Air-cooled Blastfurnace Slag | NPD |
| Volume Stability of Steel Slag Aggregates | NPD |
| Emission of Radioactivity | NPD |
| Release of other Dangerous Substances | NPD |
| Water Absorption Value | 0.99% |

Declaration of Performance

Cloburn Quarry Company confirms that the Aggregate referred to in this certificate complies with the requirement of BS EN 13043:2002

Certificate of Performance

Certification of Performance with BS EN 13043 is provided under attestation system 2+

Authorised by

Stuart Clingan,
Director

Date Valid from

08.11.19

Date valid to

Currently valid

Date of Certificate Issue

08.11.19